

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局



(43) 国际公布日:

2005年9月9日(09.09.2005)

PCT

(10) 国际公布号:

WO 2005/083468 A1

(51) 国际分类号⁷: G01V 3/30

(21) 国际申请号: PCT/CN2004/001403

(22) 国际申请日: 2004年12月2日(02.12.2004)

(25) 申请语言: 中文

(26) 公布语言: 中文

(30) 优先权:
200310113035.8 2003年12月25日(25.12.2003) CN

(71)(72) 发明人/申请人: 周仁安(ZHOU, Renan) [CN/CN];
郭自任(GUO, Ziren) [CN/CN]; 中国云南省昆明市关上双桥路290号, Yunnan 650200 (CN)。

(74) 代理人: 隆天国际知识产权代理有限公司(LUNG TIN
INTERNATIONAL INTELLECTUAL PROPERTY
AGENT LTD.); 中国北京市朝阳区慧忠路5号远大中心B座18层, Beijing 100101 (CN)。

(81) 指定国(除另有指明, 要求每一种可提供的国家保护):
AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW,
BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR,

HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL,
PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW

(84) 指定国(除另有指明, 要求每一种可提供的地区保护):
ARIPO(BW, GH, GM, KE, LS, MW, MZ, NA, SD,
SL, SZ, TZ, UG, ZM, ZW), 欧亚专利(AM, AZ, BY,
KG, KZ, MD, RU, TJ, TM), 欧洲专利(AT, BE, BG,
CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,
IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI(BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG)

根据细则4.17的声明:

— 发明人资格(细则4.17(iv))仅对美国


本国际公布:

— 包括国际检索报告。

所引用双字母代码和其它缩写符号, 请参考刊登在每期
PCT公报期刊起始的“代码及缩写符号简要说明”。

(54) Title: THE METHOD AND APPARATUS FOR MEASURING RESISTIVITY OF EARTH BY
ELECTROMAGNETIC WAVES

(54) 发明名称: 大地电磁波电阻率测量方法及其仪器



1. ELECTRIC FIELD SENSOR
2. MAGNETIC FIELD SENSOR
3. PREAMPLIFIER
4. DATA COLLECTION SYSTEM
5. SYSTEM FOR COLLECTION, CONTROL, AND DATA PROCESSING

(57) Abstract: This invention involves the method and apparatus for measuring the resistivity of earth by electromagnetic waves. The strata are sampled by sensors for electric fields, sensors for magnetic fields and data collection means. The depth coefficients are determined and the depth coefficients of the surface are corrected. The resistivities of earth, which are determined by electromagnetic waves, are consecutively measured by means of a sampling and controlling system, and a data storage and processing system on the basis of basic relationships between the depth of the stratum (H) and the transmitting frequency (F), basic relationships between the resistivity (ρ) determined by electromagnetic waves and the depth (H), and estate fishing a coordinate system for observing. The relationships between the frequencies and the depths are directly determined by utilizing the data on-the-spot survey by means of the invention. The invention modifies the traditional methods, which utilizes multiple variables theoretical equations to obtain the depth or thickness of the stratum, and makes the resistivity of the stratum to be a single variable. The invention improves the measuring precision greatly. This invention can be directly used to prospect mineral resources, decrease the number of wells, and increase the whole beneficial results of the prospect by utilizing the apparatus to process the data collected in-site, and achieving the curves of the resistivity determined by electromagnetic waves vs. the depth at any moment.

[见续页]